

MAN'GO 12

12

1111
021-6270 2802
www.maclift.cn

1 A3-403



Technical characteristics

MAN'GO 12

Capacities		Working Height 工作高度	mm	11 910
		Platform height 平台高度	mm	9 910
		Outreach 跨越高度	mm	6 690
		Overhang 水平延伸距	mm	4 800
		Jib tilting 短臂上下摆动幅度	°	+66.5 / -70
		Basket capacity 平台安全载荷	Kg	230
		Turret rotation 塔座旋转	°	350
		Basket rotation 平台旋转	°	125
		Number of persons (indoor/outdoor) 可承载人数 (室内/室外)		2
	2.1	Weight 重量	Kg	4 150*
Weight & dimensions	2.2	Basket dimensions (L x l) 平台尺寸	mm	1 500 x 987
	2.3	Overall width 宽度	mm	1 800
	2.4	Overall length 长度	mm	5 500
	2.5	Overall length when folded 储藏长度	mm	4 500
	2.6	Overall height 高度	mm	2 015
	2.7	Overall height when folded 储藏高度	mm	2 495
	2.8	Floor height (access) (进入时) 平台底板高度	mm	395
	2.9	JIB length 短臂长度	mm	1 829
	2.11	Inside turning circle 内转向半径	mm	1 715
	2.12	Outside turning circle 外转向半径	mm	4 115
Performances	2.15	Ground clearance (front of the chassis) 离地间隙	mm	320
	2.17	Wheelbase 轮距	mm	2 000
		Driving speed 行驶速度	km/h	5.2
		working speed 工作速度	km/h	0.8
		Maximum slope accessible 爬坡能力	%	40
		Maximum tilt 最大允许坡度	° / %	4 / 7
Tires		Type of tires 轮胎		Cured-on
		Dimensions (height x width) 轮胎尺寸	mm	720 x 240
		Driving wheels 驱动轮		4
		Steering wheels 转向轮		2 (front) 前轮驱动
Engine		Type of engine 发动机		Kubota D1105-E2B
		Power engine 发动机功率	kW/hp	19.4 / 26.4
Miscellaneous		Maximum available hydraulic pressure 液压最大压力	Bar	400
		Capacity of hydraulic tank 液压油油箱	L	60
		Capacity of fuel tank 燃油油箱	L	53
		Vibration level 振动	m/s ²	< 2,5
		Environmental noise (Lwa) 环境噪音	db	100
		Floor pressure (hard floor) 对地面压力	daN/cm ²	14,98
		Fuel consumption ** 燃油消耗	l/day	4.28

Equipments

standard 标配

jib 短臂

Management of engine RPM 发动机转速管理

Steel turret covers 塔座盖

Quick access to components 部件快速接近口

Simplified lift control system 简化的举升操作系统

Proportional levers 比例控制器

Simultaneous movements 同时动作

Differential lock 差速锁

Audible alarm in basket 平台警示灯

Audible and visual display alarm 倾斜、过载等警示

Dead man pedal 与操作手柄联动的脚踏板

Emergency pump 应急下降电动泵

Lifting/tie down points 吊装孔

On board Diagnostics 操作面板内置诊断器

Hour meter 小时计

Fuel gauge with low level warning 燃油指示器带低油位报警

Rotative beacon 可旋转喇叭

Protective cover for control panel 控制面板保护罩

Tool box in basket 工具箱

Optional 选配

SMS : Safe Man System 工作人员安全系统

Working light 工作灯

Non-marking tires 无痕轮胎

Battery cut off 主电源开关

Screen protection on the lower box control 车身控制箱屏保

Turret cover with key lock 可锁塔座盖

Lockable fuel cap 可锁油箱盖

Water / Air predisposition 水/压缩空气作业预设置

Onboard generator 机载发电机

Catalytic convertor 催化净化器

Anti theft code 防盗码

230V power input with differential circuit-breaker 带断路保护开关的230V插座

Warning travel alarm 驱驶警示

Warning alarm for all movements 全运动警示

Safety harness 安全带

Certificate of verification 检验证书

Biodegradable oil 可生物降解油品

Hydraulic oil four cold countries 极寒国家液压油

